





Entscheidend ist das



RICHTIGE WERKZEUG

Verarbeitungsempfehlung				Maximale Verarbeitungsmenge								
Produkt	Einheit	Werkzeug	Geschwindigkeit	PL10	PL20	PL30	PL40	PL60	PL80	PL100	PL120	PL140
Eiweiß (1L=30 Eier)	Liter		Maximal	1,0	2,0	4,0	6,0	9,0	12,0	13,0	14,0	16,0
geschlagene Sahne				3,0	5,0	8,0	10,0	16,0	25,0	28,0	32,0	40,0
Mayonnaise				7,0	10,0	12,0	13,0	18,0	24,0	30,0	36,0	50,0
Kartoffelpüree	Kilo- gramm		Mittel/Minimal	8,0	12,0	18,0	24,0	36,0	60,0	75,0	90,0	105,0
Grundteig für Gebäck/Kekse				4,0-6,0	8,0-10,0	12,0-15,0	18,0-22,0	27,0-30,0	32,0-40,0	41,0-49,0	50,0-65,0	68,0-75,0
Brotteig (55% Wasser)	Kilo- gramm		Minimal	5,0	7,0	15,0	25,0	30,0	40,0	50,0	60,0	70,0
Pizzateig (50% Wasser)				2,0	5,5	12,0	16,0	24,0	32,0	40,0	48,0	56,0
Pizzateig (40% Wasser)				3,5	4,5	9,0	12,0	18,0	24,0	30,0	36,0	42,0
Biskuitteig	Kilo- gramm		Maximal/Mittel	7,0	9,0-12,0	15,0-18,0	20,0-24,0	30,0-35,0	48,0-55,0	55,0-65,0	65,0-75,0	72,0-85,0

Werkzeuge und Zubehör		Rührmaschinen								
Zubehör	Einheit	PL10	PL20	PL30	PL40	PL60	PL80	PL100	PL120	PL140
	Rührkessel	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Reduktionskessel		✓		✓	✓	✓	✓		
	Knethaken	✓								
	Spiralknethaken	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Schlagbesen	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Rührbesen		✓	✓	✓	✓	✓	✓	✓	✓
	Rührer	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Abstreifer				✓	✓	✓	✓	✓	✓
	Kesseltransportwagen (Kessel bis 60 Liter)			✓	✓	✓				
	Kesseltransportwagen (Kessel ab 60 Liter)						✓	✓	✓	✓

Technische Daten

AUF EINEN BLICK

Technische Daten											
Maße	PL10	PL20 N	PL 20 H	PL30	PL40	PL60	PL80 N	PL80 H	PL100	PL120	PL140
Länge	770 mm	728 mm	728 mm	836 mm	926 mm	950 mm	1022 mm	1022 mm	1057 mm	1167 mm	1181 mm
Breite	407 mm	564 mm	564 mm	627 mm	685 mm	685 mm	855 mm	855 mm	855 mm	974 mm	974 mm
Höhe	616 mm	918 mm	1317 mm	1343 mm	1477 mm	1562 mm	1440 mm	1680 mm	1769 mm	1957 mm	1957 mm
Gewicht	70,0 kg	100,0 kg	100,0 kg	210,0 kg	225,0 kg	230,0 kg	360,0 kg	380,0 kg	390,0 kg	575,0 kg	595,0 kg
Elektrische Leistung	PL10	PL20 N	PL 20 H	PL30	PL40	PL60	PL80 N	PL80 H	PL100	PL120	PL140
Stromanschluss	230V	230V	230V	230V	400V*	400V*	400V	400V	400V	400V	400V
Motorleistung	0,55kW	1,1kW	1,1kW	1,5kW	2,2kW	3,0kW	4,0 + 0,75kW**	4,0 + 0,75kW**	4,0 + 0,75kW**	5,5 + 0,75kW**	5,5 + 0,75kW**
Sicherheitsschalter für Kesselerkennung	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
elektronischer Überlastschutz	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
manuelle Höhenversellung des Kessels	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
CE geprüft	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

* optional auch als 230V-Variante erhältlich / ** Sonderelektronik für elektrische Kesselanhebung